

PRODUCT INFORMATION PACKET



Model No: H947L
Catalog No: H947L
Circulator Pump Motor, 1.0 HP, 3 Ph, 60 Hz, 575 V, 1800 RPM, FA56Y Frame, ODP



Regal and Century are trademarks of Regal Rexnord Corporation or one of its affiliated companies.
©2022 Regal Rexnord Corporation, All Rights Reserved. MC017097E





Nameplate Specifications

Output HP	1.0 Hp	Output KW	0.75 kW
Frequency	60 Hz	Voltage	575 V
Current	1.4 A	Speed	1725 rpm
Service Factor	1.25	Phase	3
Duty	Continuous	Insulation Class	B
Frame	FA56Y	Enclosure	Open Drip Proof
Thermal Protection	No Protection	Ambient Temperature	50 °C
UL	Recognized	CSA	Y
CE	N	Number of Speeds	1

Technical Specifications

Electrical Type	Polyphase, Induction Type, Single Or Dual Voltage	Starting Method	Across The Line
Poles	4	Rotation	Reversible Counterclockwise
Mounting	Cushion Ring	Drive End Bearing	Sleeve
Opp Drive End Bearing	Sleeve	Frame Material	Rolled Steel
Shaft Type	Keyed	Overall Length	11.69 in
Frame Length	5.75 in	Shaft Diameter	0.625 in
Shaft Extension	1.94 in		
Outline Drawing	H947L-S01		

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:11/28/2022